

KRGS

ROLLER GRILLES
AND SHUTTERS

est. 2007



STEEL ROLLER SHUTTER DOORS

Retail and commercial
Suitable for both internal
and external use

The KRGS Steel Roller Shutters comes in a range of slat sizes including 50mm slat, 75mm slat or 100mm slat. The steel slat comes with a choice of solid, slotting or perforations depending on requirements.

Suitable applications include loading docks, industrial factory units, car parks and commercial buildings.

The KRGS Steel Roller Shutters can be slotted or perforated to provide ventilation where necessary or remain solid to keep out vermin and debris. The KRGS Steel Roller Shutters can be supplied in a vast arrange of sizes and colour finishes to suit all decors.

APPLICATIONS

- Ideal for loading docks, industrial factory units and commercial buildings
- High level of security

ARCHITECTURAL SPECIFICATION

Supply and install Steel Roller Shutter Doors manufactured by KRGS Roller Grilles and Shutters 1800 897 822.

A DOOR DESIGN WITH YOU IN MIND

STEEL ROLLER SHUTTER DOORS

KRGS
ROLLER GRILLES
AND SHUTTERS

KRGS Steel Roller Shutters are highly versatile that deliver strength and versatility.

CURTAIN Constructed of cold rollformed interlocking galvanised steel slats with face depth 50mm, 75mm or 100mm x 1mm or 0.8 thick, Note: Different profile and gauges are also available. Nylon end clips are fitted to prevent lateral movement and smooth operation. Wicket Gates for access are optional. Fire Rated Steel Shutters available.

BOTTOM RAIL Extruded aluminium angle section with rubber weather seal manufactured to interlock with curtain.

LOCKING Manually operated doors have heavy duty padbolts fitted to each side of the bottom rail to which padlocks can be fitted.

SIDE GUIDES are 100mm deep by 34mm wide extruded steel suitable for face fit.


TRACK Pressed steel channel 100mm or 75mm to give ease of operation and effective curtain control. Windlock guides are used where applicable.

BRACKETS Steel brackets 10mm thick are attached to walls by three dynabolts unless welded directly to steelwork.

DRUM Manufactured from 165mm or 220mm seamless tube attached to self-lubricating bearings rotating on a steel shaft. The shaft shall be fitted with helical spints designed to counterbalance the curtain weight throughout its operation. The drum shall be designed to give minimum deflection over the span. Slotted and perforated options are available.

OPERATION Hand lift, single or double reduction chain hoist or single or 3 phase operation with standard 240 volt reversing contractor.

FINISH Hot Dip Galvanised Finish. Whilst Dulux powder coat range is available as an optional extra.



WARRANTY A 12 month warranty against defective materials and workmanship applies.

NOTE KRGS ROLLER GRILLES AND SHUTTERS HAS A CONTINUOUS PROGRAM OF DEVELOPMENT SIZES OR CONFIGURATION OF PRODUCT MAY CHANGE AT ANY TIME. FOR THE LATEST IN DESIGN AND SPECIFICATION PLEASE CONSULT WITH KRGS BY CALLING US.

A DOOR DESIGN WITH YOU IN MIND

SYDNEY 8 Enterprise Circuit
Prestons NSW 2170
Phone 02 9608 9888
1800 987 822

Fax 02 9608 9333
Email sales@krgsdoors.com.au
Web www.krgsdoors.com.au

MELBOURNE Phone 0477 800 094
Email sales@krgsdoors.com.au
BRISBANE Phone 0447 710 947
Email sales@krgsdoors.com.au

ADELAIDE Phone 0474 418 168
Email sales@krgsdoors.com.au
PERTH Phone 0406 661 376
Email sales@krgsdoors.com.au

KRGS
ROLLER GRILLES
AND SHUTTERS